EXHIBIT 4 – PERIODIC TWISTER PROCESS

Periodic TWISTER Maintenance process

- 1. Wet floor area to be worked water only
- 2. Determine if floor needs deep cleaning
- 3. If so use Twister 400 grit red floor pad
- 4. Make alternating passes clockwise (length wise) then right angle (width wise) to that (clockwise) then then back and forth (length wise)(end to end clockwise) then side to side (clockwise) then repeat all in the counter-clockwise for a total of 8 passes keep surface wet then squeegee/wet vac up –
- 5. Rinse out used pads
- 6. Scrub floor area entirely using clean rinse water squeegee dry using regular brush on scrubber
- 7. Mix correct amount of Densifier in a garden sprayer per container instructions
- Spray Lythic Densifier in even smooth side to side pattern use micro fiber mop to work edges - observe and respray areas that seem to be drying faster than other areas – (15 minutes wet) -floor should dry somewhat evenly - let surface dry for instructed amount of time – 1 hour +
- 9. Scrub floor with regular brush on scrubber
- 10. Swap pad to the White Twister pad repeat steps 2 and 4
- 11. Swap pad to the Yellow Twister pad repeat steps 2 and 4
- 12. Swap pad to Green Twister pad repeat steps 2 and 4
- 13. Scrub floor area entirely using clean rinse water
- 14. Let floor dry completely
- 15. USING no Water place dry Green Twister pad on burnisher polish floor making overlapping passes 1 time
- 16. Dust mop
- 17. Scrub floor again let dry
- 18. Maintain floor with normal machine scrubbing for daily maintenance

- 19. Once monthly use green twister pads on a machine scrubber prior to polish/burnish
- 20. Polish/Burnish floor 1 time weekly with Twister Green pad

USING Hand held Flex tool – grind and polish method – small – hard to access areas – borders

- 1. Wet floor water only
- 2. Attach 8" red twister pad to flex tool
- 3. Adjust flex tool for low speed work
- 4. Run flex tool with red twister pad side to side as to cover entire area 8 times rotate directions to provide a more uniform grind polish
- 5. Rinse area
- 6. Dry area
- 7. Apply Densifier per instructions let dry 1 hour plus
- 8. Wet floor after dry
- 9. Using White Twister pad repeat step 4 and 5
- 10. Using Yellow Twister pad repeat steps 1, 4, and 5
- 11. Using Green Twister pad repeat steps 1, 4, and 5
- 12. Rinse floor area completely
- 13. Let dry
- 14. Using no water use dry green twister pad at higher speed polish floor making overlapping passes 1 time
- 15. Dust mop
- 16. Scrub floor again let dry

AT any time during this work if the floor is needed to return to service/use – try and finish the step your on and scrub/rinse floor